Straight Male Cord Connectors

Form Size 5-8

UL Listed to Type 4, 4X, 12 and Type 13

IP66*
SUITABILITY



Cast Aluminum



Cast Aluminum
Malleable Iron

Straight Male

N.P.T. Hub Size	Cord Diameter Inches	(mm)	Form Size	Cast Aluminum	Malleable Iron
	.88"-1.00"	(22.2-25.4)		**SHC1046**	—
1	1.00"-1.13"	(25.4-28.6)	F5	**SHC1047****	—
	1.13"-1.25"	(28.6-31.7)		**SHC1048****	—
	1.25"-1.38"	(31.7-34.9)		**SHC1049****	—
	.75"-.88"	(19.0-22.2)		**SHC1050**	—
	.88"-1.00"	(22.2-25.4)		**SHC1051**	—
1¼	1.00"-1.13"	(25.4-28.6)	F5	**SHC1052**	**SHC1052ZP**
	1.13"-1.25"	(28.6-31.7)		**SHC1053**	**SHC1053ZP**
	1.25"-1.38"	(31.7-34.9)		**SHC1054****	**SHC1054ZP**
	.75"-.88"	(19.0-22.2)		**SHC1055**	—
	.88"-1.00"	(22.2-25.4)		**SHC1056**	—
1½	1.00"-1.13"	(25.4-28.6)	F5	**SHC1057**	**SHC1057ZP**
	1.13"-1.25"	(28.6-31.7)		**SHC1058**	**SHC1058ZP**
	1.25"-1.38"	(31.7-34.9)		**SHC1059**	**SHC1059ZP**
	1.38"-1.50"	(34.9-38.1)		**SHC1061**	—
1½	1.50"-1.63"	(38.1-41.3)	F6	**SHC1062****	—
	1.63"-1.75"	(41.3-44.4)		**SHC1063****	—
	1.75"-1.88"	(44.4-47.6)		**SHC1064****	—
	1.25"-1.38"	(31.7-34.9)		**SHC1065**	—
	1.38"-1.50"	(34.9-38.1)		**SHC1066**	—
2	1.50"-1.63"	(38.1-41.3)	F6	**SHC1067**	—
	1.63"-1.75"	(41.3-44.4)		**SHC1068**	—
	1.75"-1.88"	(44.4-47.6)		**SHC1069**	—
	1.69"-1.81"	(42.9-46.0)		**SHC1070**	—
	1.81"-1.94"	(46.0-49.2)		**SHC1071**	—
2	1.94"-2.06"	(49.2-52.4)	F7	**SHC1072****	—
	2.06"-2.19"	(52.4-55.6)		**SHC1073****	—
	2.19"-2.31"	(55.6-58.7)		**SHC1074****	—
	1.69"-1.81"	(42.9-46.0)		**SHC1076**	—
	1.81"-1.94"	(46.0-49.2)		**SHC1077**	—
2½	1.94"-2.06"	(49.2-52.4)	F7	**SHC1078**	—
	2.06"-2.19"	(52.4-55.6)		**SHC1079**	—
	2.19"-2.31"	(55.6-58.7)		**SHC1080**	—
	2.31"-2.44"	(58.7-61.9)		**SHC1081****	—
	1.69"-1.81"	(42.9-46.0)		**SHC1086**	—
	1.94"-2.06"	(49.2-52.4)	F7	**SHC1088**	—
3	2.06"-2.19"	(52.4-55.6)		**SHC1089**	—
	2.19"-2.31"	(55.6-58.7)		**SHC1090**	—
	2.31"-2.44"	(58.7-61.9)		**SHC1091**	—
	2.44"-2.63"	(61.9-66.7)		**SHC1092**	—
	2.63"-2.81"	(66.7-71.4)		**SHC1093**	—
3	2.81"-3.00"	(71.4-76.2)	F8	**SHC1094**	—
	3.00"-3.25"	(76.2-82.5)		**SHC1095****	—

Note: See pages T-92 to T-101 for additional technical data and dimensional drawings.
** IP66 Suitability when used with optional metal clad O-ring shown on page T-89.*
*** Cable jacket may have to be stripped to pass through connector body.*
Form 4 aluminum and plated steel nuts are machined, bodies are cast aluminum.
F5 and larger will not be color coded.
Locknuts sold separately. See page T-89.