Product Datasheet	Catalog Home Home Page Search

CR15I -- Straight Blade Products, Commercial Series Duplex Receptacle




CR15 Series

2-Pole 3-Wire Grounding, 15A 125V, 5-15R, Side Wired Only, Smooth Nylon Face, Ivory

Product Specifications	
Product Type	 Flush Receptacles
Receptacle Style	Duplex
Face Shape	Traditional
Standard	NEMA
Amperage	15A
Voltage	125V
Poles and Wires	2 Pole, 3-Wire Grounding
Wiring Method	Side Wire Only
Hospital Grade ?	No
Receptacle Grade	Commercial Series Specification Grade
Face Style	Smooth Face
Color	Ivory
Other Available Colors	Brown, Almond, Black, Gray, Ivory, Office White, White, Light Almond
NEMA No.	5-15R
Horsepower	0.5
Type	2 Pole, 3 Wire, Grounding
Rating	15A, 125V
Certification	UL Listed, File E2186, Meets NEMA WD-6 requirements Listed to UL Standard 498, Certified to CSA, C22.2, No. 42
Terminal Screw	#8-32 Brass, Multiple Drive

Material	
Ground Screw Material	#8-32 Brass, Multiple Drive (Green)
Top Material	Nylon
Base Material	Nylon
Power Contacts Material	.031" (.8) Phosphor Bronze
Mounting Strap Material	.040" (1) Steel (Galvanized)
Auto Ground Clip Material	.032" (.8) Steel Wire
Mounting Screw Material	Steel-Zinc Plated
Dielectric Voltage	Withstands 2,000V minimum.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..
Terminal Identification	Terminals identified in accordance with UL498 (Brass, White, Green).
Terminal Accommodation	#14-#10 AWG copper stranded or solid conductor only.
Product Identification	Ratings are a permanent part of the device.
Flammability	UL 94 V2.
Operating Temperatures	Maximum continuous 75°C, minimum -40°C (w/o impact).
UPC Number	783585900056
Weight in LBs	0.200
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog



NEMA Configuration