Product Datasheet	Catalog Home Home Page Search

5362G -- Duplex Receptacles



SelectSpec light industrial, commercial and hospital grade receptacles are ideal for any project where ease of wiring, durability and reliability are required. The impact resistant nylon face is available in a variety of colors to blend into the décor of office buildings, administrative areas, schools, government facilities and retail spaces.

Product Specifications	
SELECTSPEC Product Type	Straight Blade Products
Straight Blade Product	Duplex Receptacle
Straight Blade Product Grade	Light Industrial
Straight Blade Product Style	Finder Groove Face, Back and Side Wired
Straight Blade Receptacle Rating	20A, 125V
Straight Blade Receptacle Wiring Scheme	2 Pole, 3 Wire Grounding
Straight Blade NEMA Configuration	5-20R
Straight Blade Receptacle Color	Gray
Straight Blade Listings and Approvals	UL Listed Fed Spec, CSA Certified
Features	Multiple Drive Screws, Pre-Tensioned Ground Contact, Large Oxide Cutting Terminal Screws, High Grade, Bronze Alloy Triple Wire Power Contacts.
Face	High Impact-Resistant Chemical-Resistant Nylon
Base	Thick Walled High Impact Resistant Nylon
Contacts/Blade Material	Brass Alloy
Mounting Yoke	Steel-Zinc Plated
Dielectric Voltage	Withstands 2,000V Minimum
Max Working Voltage	250V AC or DC
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30 deg C temperature rise at full rated current after 50 cycles of overload at 150% of rated direct current.
Terminal Identification	Terminals identified in accordance with UL 498 (Brass, White, Green).
Terminal Accommodation	#14 to #10 AWG Copper Conductors Only.
Product Identification	Ratings are a permanent part of the device.
Flammability	UL 94V2
Operating Temperatures	Maximum Continuous: 60 deg C, minimum: -40 deg C. (w/o impact).
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog


HUBBELL