| | |
|---|---|
| **Product Item** | Single Receptacle |
| **Wiring Scheme** | 3-Pole, 4-Wire Grounding |
| **Amperage** | 50A |
| **Voltage** | 3 Phase 250V AC |
| **Item Style** | Standard |
| **Device Color** | Black |
| **Housing Material** | Phenolic |
| **Terminal Screw Material** | Steel pressure screw- zinc plate |
| **Ground Screw Material** | Steel pressure screw- zinc plate |
| **Body Contact Carrier Material** | Black Thermoset |
| **Contact Spring Material** | .100"/.040" Brass |
| **Mounting Screw Material** | Steel-zinc-plated |
| **Ground Contact Material** | .031" Brass |
| **Bridge (Mounting Strap) Material** | .062" Steel, Zinc Plate |
| **Rivet Material** | Brass |
| **Ratings** | Molded In or Stamped On |
| **Catalog No** | Permanently ink marked on product |
| **Dielectric Voltage Withstand** | 2,000V minimum |
| **Current Interrupting** | Certified for current interrupting at full rated current |
| **Temperature Rise** | Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75. |
| **Terminal Accommodation** | #10 AWG min #6 AWG max |
| **Terminal Identification** | Terminals identified in accordance with UL 498 (X, Y, Z, White, Green) |
| **Flammability** | UL 94 VO for Receptacles and Inlets. HB or better for Plugs and Connectors. |
| | |

| | |
|---|---|
| **Operating Temperatures** | Maximum Continuous 75 C Minimum -40 C (w/o impact) |
| **Pressure Screw Material** | Steel, Zinc Plate |
| **Terminals Material** | .050" Steel |
| **Casing Material** | .062" Steel, Zinc Plate |
| **Listings** | UL/CSA |
| **UPC Number** | 783585829074 |
| **Weight in LBs** | 0.75 |