



KTL-FC16T9-CW

T9 CIRCULAR FLUORESCENT LAMP

T9 CIRCLINE
FLUORESCENT LAMP

DESCRIPTION

40W T9 | 4100K | 60 CRI

LAMP TYPE: Circline
BULB TYPE: T9
BASE TYPE: G10q (4-Pin)
WATTAGE: 40W
COLOR TEMPERATURE: 4100K
COLOR RENDERING INDEX (CRI): 60
WARRANTY: 3 Year System/2 Year Standard



PRODUCT FEATURES

- TCLP Compliant
- Complies with IEC-61199, IEC-60901

OPERATING SPECIFICATIONS

PHOTOMETRIC CHARACTERISTICS


Initial Lumens¹	2950
Mean Lumens²	2420
Lumen Maintenance	82%
Efficacy	74 lm/w

RATED AVERAGE LIFE

Ballast Type	3 Hours/Start	12 Hours/Start
Rapid Start	10,000 Hours	N/A*

* 12 Hours/Start not relevant to typical residential applications.


LUMEN MAINTENANCE



¹ Approximate initial lumens. Lumen output based upon performance after 100 hours of operating life. Measurements obtained during operation using a reference ballast under standard laboratory conditions at 25°C.
² Approximate mean lumens. Lumen output based upon performance at 40% of the lamp's rated average life. Measurements obtained during operation using a reference ballast under standard laboratory conditions at 25°C.

PHYSICAL SPECIFICATIONS

LAMP DIMENSIONS



	Min.	Max.
A (Inner Diameter 1)	13.44"	13.68"
B (Inner Diameter 2)	13.33"	13.60"
C, D (Outer Diameter)	15.61"	15.86"
E (Bulb Diameter)	1.10"	1.18"

NOMINAL OUTER DIAMETER: 16"

BASE TYPE: G10q (4-Pin)



KTL-FC16T9-CW

T9 CIRCULAR FLUORESCENT LAMP

ORDERING INFORMATION

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS
KTL-FC16T9-CW-DP	Distributor Pack (Individually Sleeved)	12	Active

CATALOG NUMBER BREAKDOWN

KTL-FC16T9-CW-DP

