



KTLD-75-UV-PS1700-42-VDIM-LS5

CONSTANT CURRENT LED DRIVER

DESCRIPTION

LED Driver | 75W | 120-277Vac Input
1400/1500/1600/1700mA Output Current | 20-42Vdc Output Voltage



Class P Class 2



RoHS Compliant



10 YEAR
LIMITED WARRANTY



ELECTRICAL SPECIFICATIONS

Input Voltage Range	120-277Vac $\pm 10\%$
Frequency	50/60 Hz
Power Factor	>0.9 at 80-100% Load Conditions
Inrush Current	$<20A$ at 120Vac Input
Max. Input Current	0.85A at 120Vac Input
THD	$<20\%$ for 80-100% Load Conditions at 120Vac Input
Load Regulation	$\pm 2\%$
Line Regulation	$\pm 2\%$
Output Tolerance	$\pm 5\%$ at Full Load Condition
Turn-On Delay Time	$<0.5s$ at Full Load Condition
Overshoot	$<10\%$ at Full Load Condition
No Load Power Consumption	$<1W$
Ripple and Noise (pk-pk)	$<10\%$
Surge Rating	2.5kV, ANSI/IEEE C62.41
Dimming	0-10V Dimming, Dim to Off
Protection	• Over Voltage Protection: Hiccup mode. Protection will trigger when load voltage exceeds specified output voltage and will auto recover after the fault mode is removed. • Over Current Protection: Hiccup mode. Protection will trigger when load current exceeds specified output current and will auto recover after the fault mode is removed. • Short Circuit Protection: Hiccup mode. Protection will trigger when short circuited and will auto recover after the fault mode is removed.

PRODUCT SPECIFICATIONS DETAILED


Catalog Number	Output Current	Max. Output Power	Output Voltage	Typical Efficiency at 120V	Typical Efficiency at 277V	Class 2	
						US	Canada
KTLD-75-UV-PS1700-42-VDIM-LS5	1400mA	58.8W	20-42Vdc	89%	90%	✓	✓
	1500mA	63W					
	1600mA	67.2W					
	1700mA	71.4W					

KTLD-75-UV-PS1700-42-VDIM-LS5

CONSTANT CURRENT LED DRIVER

WIRING SPECIFICATIONS


WIRING DIAGRAM



Input	12", UL 1015 #18AWG (Black and White)
Output	12", UL 1569 #18AWG (Red and Blue)
Dimming	12", UL 1569 #22AWG (Purple and Pink)

PHYSICAL SPECIFICATIONS

KTLD-75-UV-PS1700-42-VDIM-LS4



LS5 Case	
A	8.48"
B	1.11"
C	1.31"
D	8.90"
E	9.55"
F	0.58"
G	3.57"

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C/-40°F to 50°C/122°F
Storage Temperature	-40°C/-40°F to 80°C/176°F
Humidity	10% to 90%
MTBF	>200,000 Hours, Full Load at 25°C/77°F Ambient Temperature
Life Rating	>50,000 Hours, Full Load at 75°C/167°F Case Temperature
Maximum Case Temperature	90°C/194°F
Maximum Case Temperature (tc) for 5-Year Warranty	75°C/167°F

SAFETY AND EMC COMPLIANCE


UL/cUL	UL 8750 Class P CAN/CSA-C22.2 No. 250.13
FCC, 47CFR Part 15	ANSI C63.4:2014 - Class B
EN61000-3-2	Harmonic Current Emissions Class C

KTLD-75-UV-PS1700-42-VDIM-LS5


CONSTANT CURRENT LED DRIVER

CHARACTERISTIC CURVES


LIFETIME VS CASE TEMPERATURE




POWER FACTOR VS OUTPUT POWER




EFFICIENCY (120V)



EFFICIENCY (277V)



THD VS OUTPUT POWER



ORDERING INFORMATION

Catalog Number	Packaging Style	Pack QTY	Item Status	UPC	Easy Code
KTLD-75-UV-PS1400-54-VDIM-LS5	Carton Pack	20	Quick Ship	843654181080	DSL-70

CATALOG NUMBER BREAKDOWN

KTLD-75-UV-PS1700-42-VDIM-LS5

1
2
3
4
5
6
7
8

- | | |
|---|--|
| <p>1 Keystone Technologies LED Driver</p> <p>2 Max. Output Wattage</p> <p>3 120-277V Input</p> <p>4 Power Select Series</p> | <p>5 Max. Output Current</p> <p>6 Max. Output Voltage</p> <p>7 0-10V Dimming</p> <p>8 Case Style</p> |
|---|--|