



KT-RKIT12AC-4C-8XX-FDIM

AC LED LIGHT ENGINE



DESCRIPTION

90 CRI AC LED Light Engine



5 YEAR
WARRANTY

PRODUCT FEATURES

- L70 > 50,000 Hours
- Operating Temperature: 0°F-104°F, -18°C-40°C
- UL Classified
- High Factor >.90
- Samsung LEDs
- Suitable for Fully Enclosed Fixtures
- THD <20%
- 5% Minimum Dimming, Low Flicker
- Comes with mounting accessories
- Pre-assembled with Metal Heatsink 5VA Cover

PERFORMANCE SPECIFICATIONS

Catalog Number	Wattage	Color Temp	Lumens	Efficacy	Input Voltage	CRI	Size	Dimming Method
KT-RKIT12AC-4C-830-FDIM	12W	3000K	1100	92 lm/W	120V	>80	4" Round	Phase Dimming
KT-RKIT12AC-4C-840-FDIM	12W	4000K	1120	93 lm/W	120V	>80		Phase Dimming
KT-RKIT12AC-4C-850-FDIM	12W	5000K	1150	96 lm/W	120V	>80		Phase Dimming

COMPATIBLE DIMMERS

Manufacturer	Model Number
Lutron	S-600PR-WH
Lutron	TGCL-153PH-WH
Lutron	MACL-153MH-LA
LEVITON	WA-RXX-06674-12A

EQUIVALENCES

- 2 x 40W Incandescent
- 2 x 11W CFL
- 20W T9 Circline

For questions on additional dimmer compatibility, please contact Keystone.




KT-RKIT12AC-4C-8XX-FDIM

AC LED LIGHT ENGINE

PHYSICAL SPECIFICATIONS

4" ROUND LIGHT ENGINE



CATALOG NUMBER BREAKDOWN

KT-RKIT12AC-4C-8XX-FDIM

1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---

- 1 Keystone Technologies
- 2 Future Fit Kit
- 3 Wattage
- 4 Alternating Current
- 5 Size (3" Circular)
- 6 80 CRI
- 7 Color Temperature
- 8 Phase Control Dimming