



KT-VTLED19-2A-8XX-VDIM-P

VAPOR TIGHT FIXTURE

DESCRIPTION

2' 19W LED Vapor Tight Fixture | 120-277V Input | 0-10V Dimming | Premium Series

APPLICATION

Used for commercial and industrial rugged or outdoor applications



10 YEAR
LIMITED WARRANTY



PRODUCT FEATURES

- Traditional design, narrow body, Vapor Tight fixture, suitable for rugged, demanding applications
- Powered by Keystone 120-277V, 0-10V dimming LED driver, 10% minimum
- Smooth, diffused, impact resistant polycarbonate lens provides even lit appearance
- Stainless steel, tamper resistant lens clips (screws not included)
- Includes mounting hardware, cordgrip, and hole plug for out-of-the-box installation
- Compatible with Keystone motion and occupancy sensors, featuring high-end trim and daylight sensing.
- NEMA 4X rated enclosure
- IP66 Ingress Protection
- IK10 Impact Rating
- Ambient operating temperature:-40°C/-40°F to 50°C/122°F
- LED chip lifetime: L70 >100,000 hours @ 25°C/77°F ambient fixture temperature
- PF: > 0.95
- THD: < 20%
- UL Certified for Wet Locations
- ETL Sanitation Listed NSF/ANSI Standard 2 - Food Equipment, Splash Zone (Not for Direct Food Zone)

Disclaimer: Not suitable for car wash applications or other applications with similar heavy pressure spray and/or splashing considerations with cleaning chemicals such as petrochemical detergents (aka soaps), chlorine, and/or humidity typically above 85% for prolonged periods

PRODUCT SPECIFICATIONS


Catalog Number	Color Temperature	Nominal Length	Input Voltage	Wattage	CRI	Lumen Output	Efficacy
KT-VTLED19-2A-840-VDIM-P	4000K	2 ft.	120-277V	19W	> 82.0	2,430	128 lm/W
KT-VTLED19-2A-850-VDIM-P	5000K	2 ft.	120-277V	19W	> 82.0	2,465	130 lm/W

KT-VTLED19-2A-8XX-VDIM-P

VAPOR TIGHT FIXTURE

PHOTOMETRIC SPECIFICATIONS

LUMINOUS INTENSITY DISTRIBUTION



ZONAL LUMEN SUMMARY

Degree	Flux (Lumens)	% Luminaire
0~10°	78.3 lm	3.10%
0~20°	300.8 lm	11.92%
0~30°	633.1 lm	25.09%
0~40°	1,026.4 lm	40.68%
0~50°	1,429.2 lm	56.64%
0~60°	1,796.7 lm	71.21%
0~70°	2,094.0 lm	82.99%
0~80°	2,298.9 lm	91.11%
0~90°	2,413.3 lm	95.65%

Degree	Flux (Lumens)	% Luminaire
0~100°	2,471.5 lm	97.95%
0~110°	2,500.7 lm	99.11%
0~120°	2,514.1 lm	99.64%
0~130°	2,519.0 lm	99.83%
0~140°	2,520.4 lm	99.89%
0~150°	2,521.5 lm	99.93%
0~160°	2,522.4 lm	99.97%
0~170°	2,523.0 lm	99.99%
0~180°	2,523.2 lm	100.00%

ACCESSORIES

SENSORS

Factory-Installable OR Field-Installable (field-installable purchased separately)

✓	SUFFIX*	CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
	/MW3	KTS-MW3-UV-KO-K2	Microwave Multifunction Occupancy/Daylight Sensor Kit, Includes 120-277V input to 12V DC convertor, IP65 12V input sensor head, nomex sleeve, extension neck	843654134352	TBV-76



Microwave Sensor Kit
KTS-MW3-UV-KO-K2

* For factory installation of accessory, add suffix to fixture part number (see ordering examples and instructions on last page of spec sheet).

Note: Fixture's driver has a 10% dim minimum does not fully turn off with sensor the fixture will dim down to its lowest allowable light level.

(Accessories continued on next page)

KT-VTLED19-2A-8XX-VDIM-P

VAPOR TIGHT FIXTURE

CORD SETS

Factory-Installable OR Field-Installable (field-installable purchased separately)

✓	SUFFIX*	CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
	/515P6	KT-CS-515P-6-18/3	Cord set for high bay; 125V NEMA 5-15P; straight blade plug; 6' SJTOW cable; 18/3 wire	843654140124	UKH-26
	/L715P10	KT-CS-L715P-10-16/3	Cord set for high bays; 277V NEMA L7-15P; twist lock plug; 10' SJTOW cable; 16/3 wire	843654140131	SFV-88
	/L615P10	KT-CS-L615P-10-16/3	Cord set for high bays; 250V NEMA L6-15P; twist lock plug; 10' SJTOW cable; 16/3 wire	843654140148	ZQS-05
	/L515P10	KT-CS-L515P-10-16/3	Cord set for high bays; 125V NEMA L5-15P; twist lock plug; 10' SJTOW cable; 16/3 wire	843654140155	GVH-22
	/L715P6	KT-CS-L715P-6-16/3	Cord set for high bays; 277V NEMA L7-15P; twist lock plug; 6' SJTOW cable; 16/3 wire	843654140162	DVU-44
	/L615P6	KT-CS-L615P-6-16/3	Cord set for high bays; 250V NEMA L6-15P; twist lock plug; 6' SJTOW cable; 16/3 wire	843654140179	LCW-66
	/L515P6	KT-CS-L515P-6-16/3	Cord set for high bays; 125V NEMA L5-15P; twist lock plug; 6' SJTOW cable; 16/3 wire	843654140186	POC-82
	/NP10	KT-CS-NP-10-16/3	Cord for high bays; no plug; inners 1/2" strip on both ends; 10' SJTOW cable; 16/3 wire	843654140193	YOH-90
	/NP6	KT-CS-NP-6-16/3	Cord for high bays; no plug; inners 1/2" strip on both ends; 6' SJTOW cable; 16/3 wire	843654140216	HUB-73
	/NP15	KT-CS-NP-15-16/3	Cord for high bays; no plug; inners 1/2" strip on both ends; 15' SJTOW cable; 16/3 wire	843654140209	EYD-18



Cord Sets

* For factory installation of accessory, add suffix to fixture part number (see ordering examples and instructions on last page of spec sheet).

Note: For cord sets not listed here, please contact your Keystone sales rep.

MOUNTS AND BRACKETS

Field-Installable / Field-Use ONLY (purchased separately)

CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
KT-VTLED-45SM-1-KIT	45° steel surface mount kit for all Keystone vapor tight fixtures	843654123455	JDN-49
KT-VTLED-TPSCREW-KIT	Screws for tamper-proofing vapor tight fixtures. Includes 14 screws	NA	NA



Screws
KT-VTLED-TPSCREW-KIT


(Accessories continued on next page)



KT-VTLED19-2A-8XX-VDIM-P

VAPOR TIGHT FIXTURE

PHYSICAL SPECIFICATIONS



ORDERING INFORMATION

CATALOG NUMBER	PACK QUANTITY	UPC	EASY CODE	DLC PRODUCT ID
KT-VTLED19-2A-840-VDIM-P-CP	4	843654122113	PJU-14	PXBOLJOW PLTP9MN4
KT-VTLED19-2A-850-VDIM-P-CP	4	843654122120	MJI-77	P5G4KSEA PUG7HVIE

CATALOG NUMBER BREAKDOWN

KT-VTLED19-2A-8XX-VDIM-P

1	2	3	4	5	6	7	8	9	10
1 Keystone Technologies	2 Vapor Tight LED Fixture	3 Wattage	4 2' Nominal Length	5 Lamp Type	6 80 CRI	7 Color Temperature	8 0-10V Dimming	9 Premium Series	10 Sensor Options
									No Option
							/MW3		Microwave Sensor Included

ORDERING EXAMPLES

FIXTURE WITH MULTIPLE FACTORY-INSTALLED ACCESSORIES*

KT-VTLED19-2A-8XX-VDIM-P/MW3/NP10

FIXTURE WITH TWO FACTORY-INSTALLED ACCESSORIES*

KT-VTLED19-2A-8XX-VDIM-P/MW3/NP10

FIXTURE WITH SINGLE FACTORY-INSTALLED ACCESSORY

KT-VTLED19-2A-8XX-VDIM-P/MW3

FIXTURE WITH NO FACTORY-INSTALLED ACCESSORIES

KT-VTLED19-2A-8XX-VDIM-P

KEYSTONE FIXTURE

CATALOG NUMBER
KT-VTLED19-2A-8XX-VDIM-P

SENSORS

✓	SUFFIX	CATALOG NUMBER
✓	/MW3	KTS-MW3-UV-KO-K2

CORD SETS

✓	SUFFIX	CATALOG NUMBER
✓	/NP10	KT-CS-NP-10-16/3

* When ordering more than one factory-installed accessory, use multiple suffixes as shown in the ordering examples above.

Note: All accessories can also be ordered separately for field installation using just their regular Catalog Number, UPC, or Easy Code.