

Extra Duty While-In-Use Covers

The new Leviton Extra Duty While-in-Use Covers are ruggedly constructed to protect from moisture, debris and insects, while providing easy access to receptacles. These non-metallic covers are available in both vertical and horizontal configurations for a secure fit and neat appearance when mounted. The UV resistant polycarbonate cover and base protect wiring devices from the elements without breaking, cracking or discoloration. Stainless steel hinge pins offer added strength and resistance to the rigors of daily use.

The Extra Duty While-in-Use Covers are available in solid Gray or Clear with a gray base. They are ideal for use with lawn equipment, pools, hot tubs, holiday and landscape lighting, outdoor entertainment systems, barbeques, fountains, vending machines and other outdoor electrical applications.

Our Extra Duty While-in-Use Covers are built to withstand the elements and feature:

- Compliance with NEC® 2014 Section 406.9(B)(1) for "Extra Duty" applications hoods*
- Standard opening accommodates Decora® GFCI devices and additional adapter plates are included for duplex and single receptacle openings
- Pre-mounted heavy-duty gasket provides a weather-resistant seal which protects from moisture and adds to ease of installation
- Includes two inserts to cover the circular cord openings to prevent insects and debris from entering the cover while not in use
- Safety lock feature
- cULus listed



Ordering Information

Item	Item Description	Configuration	Color
001-05980-UCL	While in Use Cover for GFCI/Decora, Duplex & Single Receptacle	Vertical	Clear
002-05980-UGY	While in Use Cover for GFCI/Decora, Duplex & Single Receptacle	Vertical	Gray
001-05981-UCL	While in Use Cover for GFCI/Decora, Duplex & Single Receptacle	Horizontal	Clear
002-05981-UGY	While in Use Cover for GFCI/Decora, Duplex & Single Receptacle	Horizontal	Gray

* 406.9 Receptacles in Damp or Wet Locations

(B) Wet Locations

(1) Receptacles of 15 and 20 Amperes in Wet Location. Receptacles of 15 and 20 amperes installed in a wet location shall have an enclosure that is weatherproof whether or not the attachment plug cap is inserted. An outlet box hood installed for this purpose shall be listed and shall be identified as "extra duty." All 15- and 20-ampere, 125- and 250-volt nonlocking-type receptacles shall be listed weather-resistant type.

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747-3138
Telephone: 1-800-323-8920 FAX: 1-800-832-9538
Tech Line (8:30AM-7:00PM E.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9
Telephone: 1-800-469-7890 FAX: 1-800-563-1853

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290
Telephone: (+52) 55-5082-1040 • www.leviton.com.mx



Visit our Website at: www.leviton.com

© 2014 Leviton Manufacturing Co., Inc. All rights reserved.

