

L7985-100

Support Grip, 0.70-0.85"



Representative image shown

UPC Code : 078477212950

Country Of Origin : India

RoHS Compliant : Yes

Support, Service Drop Grip, Single Eye Service Drop Grip, 0.70-0.85" Galv- Breakload is 1,900 LB

- Leviton wire mesh grips are built tough to provide the strength, reliability, and gripping force required for today's demanding wire mesh applications
- Support grips distribute the weight of the vertical or sloping runs of electrical and fiber optic cable, metal rods, tubing or hose over the entire length of the grip so the cable is not damaged
- Use of support grips avoids stress on cable connections and provides needed support for vertically hung cables

Technical Information

Material Specifications

Mesh Material : Galvanized Wire

Mechanical Specifications

Approx. Break Strength : 1900 lbs (862 kg)

Bale Length : 9 in (228.6 mm)

Cable Range : 0.70 - 0.85 in (18 - 22 mm)

Duty : Light

Eye Type : Single

Mesh Length : 8.5 in (216 mm)

Mesh Style : Closed

Standards and Certifications : UL

Weave : Single Weave

Workload Safety Factor (lbs) : 190 lbs (86.2 kg)

Product Features

Device Type : Support Grip

Warranty

Warranty : 1-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

