Single Position Solar Sockets

100 amp | 4 Terminal | 600 VAC



U5934-XL-BLG



U6087-XL-INS



U4175-RL-BLG

100 amp | 4 Terminal | Residential Solar Sockets | Standard Neutral

Catalog Number	Socket Type	Service	Hub	Connectors CU/AL		Dimensions			Knockouts			
				Line	Load	D"	W"	H"	1	2	3	4
U4175-RL-BLG*	Ringless	OH/UG	H.O.	#14-1/0	#14-1/0	3 5/16	8	11 1/2	2	1 1/2	1 1/4	1/4
U6087-XL*	Ring Type	OH/UG	C.P.	#14-1/0	#14-1/0	3 5/16	8	11 1/2	2	1 1/2	1 1/4	1/4
U6087-XL-INS*	Ring type	OH/UG	C.P.	#14-1/0	#14-1/0	3 5/16	8	11 1/2	2	1 1/2	1 1/4	1/4

100 amp | 4 Terminal | Residential Solar Sockets | Integral Isolated Neutral Option

Catalog Number	Socket Type	Service	Hub	Connectors CU/AL		Dimensions			Knockouts			
				Line	Load	D"	W"	H"	1	2	3	4
U5929-XL-INS	Ring Type	OH/UG	C.P.	#14-1/0	#14-1/0	3 5/16	8	11 1/2	2	1 1/2	1 1/4	1/4
U5934-XL-BLG	Ringless	OH/UG	C.P.	#14-1/0	#14-1/0	3 5/16	8	11 1/2	2	1 1/2	1 1/4	1/4

Notes

- **-BLG:** Barrel lock guard knockout provision.
- **Hubs:** Accepts standard meter socket hubs.
- **Construction:** Units are Type 3R for durable outdoor use, lockable and sealable.

***Application:** the standard bonded neutral units are applicable in areas where utility does not require an isolated neutral.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

MILBANK ENERGY AT WORK