

LED BOLLARDS



Product Specification

P/N	ERB800	RBL300	RBL200	SRB800	RBL400	SSB600
Size and Shape	Round 8"				Round 6"	Square 6"
Height (to luminous center)	37"			35"	30"	36"
Driver	120-347Vac, 50/60 Hz, 0-10V Dimmable					
Wattage	15-20-25W adjustable		25W	15-20-25W adjustable		
Efficacy	120 lm/W	105 lm/W	70 lm/W	120 lm/W		
CCT	3000K-4000K-5000K adjustable					
CRI	>70					
Distribution	120°-180°-360° adjustable	360°		120°-180°-360° adjustable		90°-180°-360° adjustable
Photocell	with on/off switch		not available		with on/off switch	
Surge Protection	Built-in Surge Protection: 4kV/6kV					
Emergency Backup	(optional) 7W, 90 mins, starting temp. from -20°C					
Ingress Protection	IP65					
Life Span	L70 > 50,000 hours @25°C					
Certification	UL Listed for Wet Locations					
DLC 5.1	Premium	Not Listed		Premium		
Warranty	5-year warranty					
Accessory	Optional reinforced sleeve for enhanced vandal resistance					

Lighting your Way Home, Bright and Safe

Morelux bollards provide reliable and adaptable lighting solutions for pathways, parks, campuses, and high-end facilities.

With features like adjustable CCT, wattage, and distribution zone, our bollards adapt to almost any environment. The IP65-rated housing ensures lasting protection, DTD photocell saves energy and emergency backup enhances security. Reinforced sleeve provides vandal-resistance protection.

MORELUX LIGHTING LIMITED

China Office: 17/F Guangbo Mansion, #1357, Yinxian Avenue Yinzhou District, Ningbo, China 315100

US Office: PO Box 697 Conover, North Carolina 28613

China Factory: No.399 Longfei Road, Yunlong Town, Yinzhou District, Ningbo, China 315137

Malaysia Factory: No.14, Jalan Anggerik Mokara 31/50, Seksyen 31, Kota Kemuning, 40460 Shah Alam, Selangor

Tel: +86-574-87979359 / Fax: +86-574-87717000

Email: info@morelux.com Web: www.morelux.com