

VERSAPRO[®] SERIES

13.4 SEER2 Package Gas Electric

MPG**S***MO13C




- ✓ Included LP Conversion Kit
- ✓ Quiet Multi-Speed Blower
- ✓ Durable Build & Finish
- ✓ Direct Spark Ignition
- ✓ High Quality Heat Exchanger
- ✓ Horizontal or Downflow Installation
- ✓ 81% AFUE
- ✓ Convenient Access Panels



**CHARGED WITH
R-454B
REFRIGERANT**

SCAN HERE >

for the latest version
of this brochure.



V 07.21.2026

VersaPro® Series

13.4 SEER2 Package Gas/Electric

MPGS***M013C**



The MRCOOL® VersaPro® 13.4 SEER2 Gas/Electric Package Unit is an all-in-one solution for year-round climate control. It seamlessly combines an energy-efficient 13.4 SEER2 air conditioner with a powerful 81% AFUE gas furnace—delivering reliable performance, lower utility bills, and lasting value.

Designed for both horizontal and downflow applications, this versatile unit adapts easily to your space. Plus, conversion to propane is quick and hassle-free with the included LP kit. For affordability, flexibility, and dependable comfort, VersaPro® delivers.



*Data provided by AHRI



Intertek
3124627

MODEL NO.		Unit	MPG24S060M013C	MPG30S060M013C	MPG36S090M013C	MPG42S090M013C	MPG48S090M013C	MPG60S110M013C
PERFORMANCE								
Power Supply		V-Hz, Ph	208/230 - 60, 1	208/230 - 60, 1	208/230 - 60, 1	208/230 - 60, 1	208/230 - 60, 1	208/230 - 60, 1
Cooling Capacity		Btu/h	22800	28400	34000	40000	47000	57000
	SEER2	Btu/W	13.4	13.4	13.4	13.4	13.4	13.4
Heating Input		Btu/h	60000	60000	90000	90000	90000	110000
	Output	Btu/h	48000	48000	72000	72000	72000	88000
Sound Rating		dB(A)	79	79	79	80	80	80
ELECTRICAL DATA								
Min/Max Voltage		V	187/253	187/253	187/253	187/253	187/253	187/253
Max Current Ampacity (MCA)		A	18.8	21.5	25.2	29.9	36.4	41.4
Max Current Over Protection (MOP)		A	25	30	40	45	50	60
COMPRESSOR								
Rated Load Amps (RLA)		A	11	13	16	19	23	27
Locked Rotor Amps (LRA)		A	55	58	72	86	95	125
OUTDOOR FAN MOTOR								
Outdoor	Horsepower	HP	1/12	1/6	1/6	1/3	1/3	1/3
	Full Load Amps (FLA)	A	0.8	1.0	1.0	1.9	1.9	1.9
	Rated Airflow	CFM	2,144	2,909	2,909	5,223	5,223	5,223
INDOOR BLOWER MOTOR								
Indoor	Horsepower	HP	1/2	1/2	1/2	1/2	3/4	3/4
	Full Load Amps (FLA)	A	4.2	4.2	4.2	4.2	5.7	5.7
	Rated Airflow @ .58 inwc	CFM	800	930	1050	1400	1700	1800
DIMENSIONS								
Net (WxDxH)		inch	50.68 x 35.06 x 46.43	50.68 x 35.06 x 46.43	50.68 x 35.06 x 46.43	51.56 x 44.81 x 49.75	51.56 x 44.81 x 49.75	51.56 x 44.81 x 49.75
Packing (WxDxH)		inch	51.43 x 37 x 48.62	51.43 x 37 x 48.62	51.43 x 37 x 48.62	52.12 x 45.25 x 52.37	52.12 x 45.25 x 52.37	52.12 x 45.25 x 52.37
Net Weight		lbs	422	432	444	539	560	562
Gross Weight		lbs	443	458	467	559	581	584
REFRIGERANT								
Refrigerant Type		Type	R-454B	R-454B	R-454B	R-454B	R-454B	R-454B
Refrigerant Charge		oz	42	44	46	60	60	60