EASY-TWIST™
Wire Connectors
Winged Twist-On
WWC Series

LISTED 231168 RoHS COMPLIANT

FEATURES
- Deep surface ridges provide better grip.
- Ergonomic, swept-back wing design provides handling comfort and increased torque ability.
- Flame retardant UL 94V-2 thermoplastic shell provides excellent electrical insulation.
- Fixed, precise square wire spring provides secure gripping of conductors.
- Deep skirt entry provides protection from flashover and shorts.
- Compact design ensures proper installation, especially in tight spaces.
- Threaded funnel entry guides the wires into the connector easily.
- Pre-twisting of wires is not necessary.
- Zinc-plated springs for low contact resistance.
- **Installation:** Socket installation tools are included in each bag of Easy-Twist™ Connectors (Cat.No. with "-B" suffix). Made to fit any pneumatic or electrical tool with a 1/4" chuck or drive socket.

SPECIFICATIONS
- UL 486C Listed wire connector E155027.
- WWC-GR is UL 467 Listed Grounding and Bonding.
- **Temperature Rating:** 105 °C (221 °F).
- **Voltage:** 600V max., 1,000V max. in fixtures and signs.
- **Wire Type:** For Copper wire only.
- **Example: (100) (10x100) = 100 in standard package, 1000 in standard carton.**

CARTON	SMALL JAR	LARGE JAR	LARGE BAG	BUCKET	BULK	DRUM
						

COLOR/TYPE	CARTON	SMALL JAR	LARGE JAR	LARGE BAG	BUCKET	BULK	DRUM
Yellow (WWC)	**WWC-Y-C** (100) (10X100)	**WWC-Y-CJ** (100) (50x100)	**WWC-Y-J** (550) (12x550)	**WWC-Y-B** (500) (13x500)	**WWC-Y-BT** (3,000)	**WWC-Y** (5000)	**WWC-Y-D** (35000)
Tan (WWC)	**WWC-T-C** (100) (10x100)	**WWC-T-CJ** (100) (50x100) **WWC-T-SJ** (100) (50x100)	**WWC-T-J** (450) (12x450)	**WWC-T-B** (500) (12x500)	**WWC-T-BT** (3,000)	**WWC-T** (5000)	**WWC-T-D** (30000)
Red (WWC)	**WWC-R-C** (100) (10x100)	**WWC-R-SJ** (100) (20x100)	**WWC-R-J** (300) (12x300)	**WWC-R-B** (500) (7x500)	**WWC-R-BT** (3,000)	**WWC-R** (5000)	**WWC-R-D** (20000)
Grey (WWC)	**WWC-G-C** (50) (10x50)	**WWC-G-SJ** (50) (32x50)	–	**WWC-G-B** (250) (11x250)	–	**WWC-G** (5000)	**WWC-G-D** (20000)
Blue (WWC)	**WWC-B-C** (50) (10x50)	**WWC-B-SJ** (50) (20x50)	**WWC-B-J** (125) (12x125)	**WWC-B-B** (100) (16x100)	–	**WWC-B** (2500)	**WWC-B-D** (9500)
Green GND (WWC)	**WWC-GR-C** (100) (10x100)	**WWC-GR-SJ** (100) (20x100)	**WWC-GR-J** (300) (12x350)	**WWC-GR-B** (500) (9x500)	**WWC-GR-BT** (3,000)	**WWC-GR** (5500)	**WWC-GR-D** (25000)
Yellow N1 (WWC)	**WWC-N1-C** (100) (10X100)	**WWC-N1-CJ** (100) (50x100)	–	**WWC-N1-B** (500) (13x500)	–	**WWC-N1** (10000)	–
Red N2 (WWC)	**WWC-N2-C** (100) (10X100)	–	–	**WWC-N2-B** (500) (9x500)	–	**WWC-N2** (10000)	–

Scan **QR code** for mobile access to wire combinations.