THREAD INSTALL ROD HANGER WITH ANGLE BRACKET, 0.25" HOLE 1, PLAIN, 0.375" HOLE 2, THREADED

CATALOG NUMBER

6TIB



CERTIFICATIONS

FEATURES

Suspends threaded rod from horizontal structures such as laminated wood or concrete beams, joists, ceilings and walls

PRODUCT ATTRIBUTES

Material: Spring Steel;Steel
Finish: nVent CADDY Armour;Pregalvanized
Hole Size 1: 1/4"
Hole Type 1: Plain
Hole Size 2: 3/8"
Hole Type 2: Threaded
Static Load: 160 lb

ADDITIONAL PRODUCT DETAILS

Loads indicated are for nVent CADDY Fasteners only.

Method of attachment to structure must be evaluated separately.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

© 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.