

SPECIFICATION & FEATURES

DESCRIPTION:

Orbit's Universal Mounting Adjustable 4" Octagon Box (UMAB-4R) is a fast, efficient way to install lighting fixtures, smoke detectors and devices where drywall depths are unknown. Built-in adapter allows for adjustment of the 2-1/8" deep, 4O box from 0" to 1-1/2", ensuring devices and trims sit flush with wall surfaces. UMAB-4R's mount direct to stud frames. Mount UMAB-4R's between studs or joists with Orbit's SSB; or between drop ceiling grids with SSB-TBAR. UMAB-4R includes 10" grounding pigtail. FA-UMAB-4R is powder coated red for quick identification of FA devices.

UNIVERSAL MOUNTING ADJUSTABLE 4" OCTAGON BOX



UMAB-4R



FA-UMAB-4R



FEATURES:

- Best way to mount lighting fixtures, sensors, smoke detectors and devices compatible with 4O openings in walls and ceilings
- Built-in adapter allows box adjustment from flush to 1-1/2" via guided slots (ships with box set at 5/8" raise)
- Two (2) outside-facing screws lock box at desired depth
- UMAB-4R includes 10" Solid Cu. #12AWG Pigtail and 10-32 Ground Screw
- Designated holes on adapter are approved for branch line restraints
- FA-UMAB-4R is powder coated red for quick identification of FA devices
- Patented

SPECIFICATIONS:

Box Dimensions

- Diameter: 4"
 - Depth: 2 - 1/8"
 - Volume: 21.5 Cu.In.
 - Material: 16 GA Sheet Steel
 - Mfg. Process: Welded
 - Color: Galvanized
 - KO Sides: (2) - 1/2", (2) - MKO
 - KO Bottom: (3) - 1/2", (2) - 3/4"
- (Side K.O.s may not be accessible)

APPLICATIONS:

- "Disc" or "wafer" style LED downlight modules
- Motion and occupancy sensors
- Smoke detectors
- Mount between wall studs or hard lid ceiling joists with SSB or SSB-T5
- Mount in drop ceiling grids with SSB-TBAR (UMAB-4R also available pre-assembled as SSBT-4R)

CONFIGURATION DATA:

Part No.	Description	Std.Pkg.
UMAB-4R	4" (4O), 2-1/8" DEEP WELDED OCTAGON BOX WITH BUILT-IN ADAPTER AND 10" PIGTAIL, ADJUSTABLE FROM FLUSH UP TO 1-1/2"	20
FA-UMAB-4R	RED 4" (4O), 2-1/8" DEEP WELDED OCTAGON BOX WITH BUILT-IN ADAPTER, ADJUSTABLE FROM FLUSH UP TO 1-1/2"	20

