THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.


PART NUMBER		TAB SIZE	AWG WIRE RANGE (mm^2)	HOUSING COLOR	MAX WIRE INSUL DIA	DIMENSIONS in.			
PREFIX	PK					A ±.03 (,8)	B ±.02 (,5)	W ±.01 (,3)	X ±.03 (,8)
DNFR18-250B	-L -M	.250 X .032 (6,3 X 0,8)	22-18 (0,5-1,0)	RED	.130 (3,30)	.78 (19,8)	.20 (5,1)	.36 (9,1)	.62 (15,7)
DNFR14-250B	-L -M	.250 X .032 (6,3 X 0,8)	16-14 (1,5-2,5)	BLUE	.155 (3,94)	.78 (19,8)	.20 (5,1)	.36 (9,1)	.63 (16,0)
DNFR18-205B	-L -M	.205 X .032 (5,2 X 0,8) OR .187 X .032 (4,8 X 0,8)	22-18 (0,5-1,0)	RED	.130 (3,30)	.78 (19,8)	.20 (5,1)	.36 (9,1)	.62 (15,7)
DNFR14-205B	-L -M	.205 X .032 (5,2 X 0,8) OR .187 X .032 (4,8 X 0,8)	16-14 (1,5-2,5)	BLUE	.155 (3,94)	.78 (19,8)	.20 (5,1)	.36 (9,1)	.63 (16,0)
DNFR18-206B	-L -M	.205 X .020 (5,2 X 0,5) OR .187 X .020 (4,8 X 0,5)	22-18 (0,5-1,0)	RED	.130 (3,30)	.78 (19,8)	.20 (5,1)	.36 (9,1)	.62 (15,7)
DNFR14-206B	-L -M	.205 X .020 (5,2 X 0,5) OR .187 X .020 (4,8 X 0,5)	16-14 (1,5-2,5)	BLUE	.155 (3,94)	.78 (19,8)	.20 (5,1)	.36 (9,1)	.63 (16,0)

LISTED 20H3 E78522

CERTIFIED LR31212

NOTES:

1. USED FOR:
   A. 600V MAX VOLTAGE RATING
   B. 221°F (105°C) MAX INSULATION TEMP. RATING
   C. STRANDED COPPER WIRE ONLY
2. FIRST INSERTION FORCE - 12 LB. (53N) MAX
   FIRST WITHDRAWAL FORCE - 12 LB. (53N) MAX
   6 LB. (27N) MIN
3. INSTALLATION TOOLS:
   A. CT-1525
4. WIRE STRIP LENGTH: 9/32 $^{+1/32}_{-0}$ (7.1 $^{+.8}_{-0}$)
5. MATERIAL USED:
   A. TERMINAL STAMPING: .018 (.46) (THK) TIN PLATED BRASS
   B. HOUSING : NYLON
6. PACKAGING QTY:
   A. STD : -L = 50
   B. BULK: -M = 1000
7. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS OR mm^2



PANDUIT CORP. TINLEY PARK, ILLINOIS

MOLDED NYLON INSULATED RIGHT ANGLE FEMALE DISCONNECTS, BUTTED SEAM

REV	DATE	BY	DESCRIPTION
07	1/11	SRB	CHANGED PACKAGING CODE FROM C=100 TO L=50

DRAWN BY	CHK'D	SCALE	DRAWING NO.
DAW	RLS	NONE	A41329