

LT Flexible Metallic Conduit - Galvanized Core

Stainless



Description

Robroy Stainless Liquid Tight Flexible Metallic Conduit is designed for use with liquid tight connectors. Robroy Stainless Liquid Tight Flexible Metallic Conduit is coated with an FDA-compliant thermoplastic PVC antimicrobial jacket and can be used in wet or dry locations and is available with a galvanized core for splash zones.

Standards

- cULus Listed
- UL 360
- NSF/ANSI 169
- UL File Number: E514740

Catalog No.	Description	Weight Per 100 Feet (lbs.)	Overall Length (ft.)	Outside Diameter (in.) Min-Max
RSFGLFMCGS-038	Liquid Tight Flexible Metallic Conduit 3/8 Inch Galvanized Core	25	100	.690-.710
RSFGLFMCGS-050	Liquid Tight Flexible Metallic Conduit 1/2 Inch Galvanized Core	29	100	.822-.840
RSFGLFMCGS-075	Liquid Tight Flexible Metallic Conduit 3/4 Inch Galvanized Core	44	100	1.030-1.050
RSFGLFMCGS-100	Liquid Tight Flexible Metallic Conduit 1 Inch Galvanized Core	73	100	1.290-1.315
RSFGLFMCGS-125	Liquid Tight Flexible Metallic Conduit 1-1/4 Inch Galvanized Core	100	50	1.630-1.660
RSFGLFMCGS-150	Liquid Tight Flexible Metallic Conduit 1-1/2 Inch Galvanized Core	112	50	1.865-1.900
RSFGLFMCGS-200	Liquid Tight Flexible Metallic Conduit 2 Inch Galvanized Core	148	50	2.340-2.375

Available in standard lengths only, not available to order "cut to length"