

PLASTI-BOND REDH₂OT SUPPORT PRODUCTS

PLASTI-BOND REDH₂OT COATED PIPE STRAPS AND STEEL STRUTS

Coated Pipe Straps

[Print This Page](#)

[Return To Index](#)

APPLICATION

PLASTI-BOND PVC coated pipe straps are used with coated strut to support conduit installations in a variety of configurations. PBC105 style straps may be used in either vertical or horizontal positions to support conduit. Straps provided with stainless steel hardware. Conduit spacing may be as close together as allowed by the couplings. PBC149 style straps may be used with hanger rods or other means of support to securely fasten conduit runs.

FEATURES

- 20 mil gray PVC exterior coating
- Available in 11 trade sizes.



PVC COATED PIPE STRAPS

Size	FERROUS Catalog #	Gauge Metal	Weight For 100 pcs	Standard Pack
☐ 1/2"	PBC149-1/2		18	25
☐ 3/4"	PBC149-3/4		21	25
☐ 1"	PBC149-1		22	25
☐ 1-1/4"	PBC149-1-1/4		25	25
☐ 1-1/2"	PBC149-1-1/2		27	25
☐ 2"	PBC149-2		29	25
☐ 2-1/2"	PBC149-2-1/2		64	25
☐ 3"	PBC149-3		72	25
☐ 3-1/2"	PBC149-3-1/2		84	25
☐ 4"	PBC149-4		138	10
☐ 5"	PBC149-5		162	10

PVC COATED PIPE STRAPS

Size	FERROUS Catalog #	Gauge Metal	Weight For 100 pcs	Standard Pack
1/2"	PBC105-1/2	14	13.0	100
3/4"	PBC105-3/4	14	15.0	100
1"	PBC105-1	14	17.0	100
1-1/4"	PBC105-1-1/4	12	19.5	100
1-1/2"	PBC105-1-1/2	12	28.0	100
2"	PBC105-2	12	31.0	50
2-1/2"	PBC105-1-1/2	12	36.0	50
3"	PBC105-3	12	42.0	50
3-1/2"	PBC105-3-1/2	11	56.0	25
4"	PBC105-4	11	64.0	25
5"	PBC105-5	10	76.0	25


PVC Coated Ferrous Strut Specifications

APPLICATION

PLASTI-BOND PVC coated strut is a versatile system of structural elements that can be used to build supports for a variety of applications. When combined with coated conduit hangers and other accessories, coated strut is a versatile and economical way to provide reliable support for conduit runs and other electrical and mechanical installations.

FEATURES

- 20 mil gray PVC exterior coating
- 2 trade sizes and 3 standard styles



PVC COATED STRUT

Style	FERROUS Catalog #	Nominal Wt. Per 100 ft.	X	Y	Strut Thickness
☐ Channel	PBP1000-10	200.0	1.67	1.67	12 ga.
☐ Channel Slotted	PBSH1000-10	185.0	1.67	1.67	12 ga.
☐ Channel Back to Back	PBP1001-10	380.0	1.67	3.29	12 ga.
☐ Channel Shallow	PBP3300-10	135.0	1.67	0.92	12 ga.
☐ Channel Slotted	PBSH3300-10	130.0	1.67	0.92	12 ga.

PVC COATED STRUT CUT-TO-LENGTH

FERROUS Catalog #	Description	X	Y	Length In Ft.	Strut Thickness
☒ PBP1000-1	1-5/8 CHANNEL	1.67	1.67	1	12 ga.
☒ PBP1000-1-1/2	1-5/8 CHANNEL	1.67	1.67	1-1/2	12 ga.
☒ PBP1000-2	1-5/8 CHANNEL	1.67	1.67	2	12 ga.
☒ PBP1000-2-1/2	1-5/8 CHANNEL	1.67	1.67	2-1/2	12 ga.
☒ PBP1000-3	1-5/8 CHANNEL	1.67	1.67	3	12 ga.
CHANNELS WITH SLOTTED HOLES					
☒ PBSH1000-1	1-5/8 CHANNEL	1.67	0.92	1	12 ga.
☒ PBSH1000-1-1/2	1-5/8 CHANNEL	1.67	0.92	1-1/2	12 ga.
☒ PBSH1000-2	1-5/8 CHANNEL	1.67	0.92	2	12 ga.
☒ PBSH1000-2-1/2	1-5/8 CHANNEL	1.67	0.92	2-1/2	12 ga.
☒ PBSH1000-3	1-5/8 CHANNEL	1.67	0.92	3	12 ga.

PVC Coated Strut Nut Specifications

APPLICATION

PLASTI-BOND PVC coated strut nuts are used to assemble strut components and to secure coated all thread rod in a section of strut. These are available with or without a spring to aid in placement and assembly.

FEATURES

- 20 mil gray PVC exterior coating
- 10 trade sizes from 1/2" through 4".



COATED STRUT NUT

Pipe Size	FERROUS Catalog #
☐ 3/8"	PBB910-3/8
☐ 1/2"	PBB910-1/2
☐ 3/8"	PBB911-3/8
☐ 1/2"	PBB911-1/2
☐ 3/8"	PBB914-3/8
☐ 1/2"	PBB914-1/2