
THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT – By – ALL RIGHTS RESERVED.

LOC	DIST
G	14

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	G1	REVISED PER ECO-11-004587	11MAR11	RK	HMR



METRIC

DIMENSIONS LISTED IN mm [INCHES]

AMP WIRE RANGE	E13288 Listed
12–10 AWG SOLID OR STRANDED	12–10 AWG STRANDED

LR7189 Certified	MILITARY P/N AND CLASS
12–10 AWG SOLID OR STRANDED	MS20659–105 CLASS 1 & 2 P/N 33457 CLASS 2 P/N 2–33457–2

1 STAMP AMP 12–10* APPROX AS SHOWN

AMP INCORPORATED CUSTOMER SERVICE SYSTEMS		MAX RECOMMENDED OPERATING TEMPERATURE: 170° C MAX
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS	PRODUCT INFORMATION CENTER 1–800–522–6752	VOLTAGE RATING: NOT APPLICABLE
FOR APPLICATION TOOLING INFORMATION	TOOLING ASSISTANCE CENTER 1–800–722–1111	WIRE CROSS SECTIONAL AREA RANGE: 2.62–6.64mm² [5,180–13,100] CIR MILS SOLID OR STRANDED
FOR ORDER ENTRY	1–800–526–5142	THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

QUANTITY	PACKAGING TYPE	PART NO
25	LOOSE PIECE, BAG	8–33457–5
100	LOOSE PIECE, BOX	8–33457–1
2500	ON TAPE	2–33457–2
----	LOOSE PIECE	33457

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL: COPPER PER ASTM B–152 ANNEALED

FINISH: TIN PLATE 0.00254[.000100] MIN THK PER MIL–T–10727

DWN TA BRINKMAN 3–17–93
CHK DA PATTERSON 3–17–93
APVD DE MILLER 3–17–93
PRODUCT SPEC –
APPLICATION SPEC –
WEIGHT –

TE Connectivity

NAME: TERMINAL, RING TONGUE, SOLISTRAND™ –

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-33457	–

CUSTOMER DRAWING | SCALE 10:1 | SHEET 1 OF 1 | REV G1

33457