

Catalog:	
Project:	
Type:	Date:
Notes:	

LED EXIT LIGHT

TK-EE-7007™ Series

Description

Tektron's EE-7007 LED Exit Light features fully illuminated 6-inch characters with long-life, high-intensity LEDs. Designed with a universal, field-selectable single- or double-face configuration, it supports wall, end, and ceiling mounting. Constructed with flame-retardant thermoplastic ABS housing.

Applications

This Luminaries is suitable for using in Wet location, on Malls/Retail Spaces, Hotels, Hospitals, residential.

Quick Ship

TK-EE-7007R
TK-EE-7007G



Specification Features

Controls / Dimming

The device features an injection-molded thermoplastic ABS housing, and is powered by a maintenance-free 3.6V NiCad battery.

Certifications

It complies with UL listings.

Warranty

5 Years Limited Warranty.
For more information visit us at,
www.technoledlights.com/warrantyinfo

Installation / Mounting

The installation process is straight forward and offers a range of mounting possibilities. Wall, end and ceiling

Ordering Information


Example: TK-EE-7007RX-R-RC

TK	EE-7007	R	RC	[Blank]
Brand	Series	Letter Color	Option	Voltage
TK - TekTron	EE-7007R Emergency Exit 7007 Series	R - Red G - Green	RC- Remote Capacity TP- Tamper Proof Screws SDT- Self Diagnostics CW- Cold Weather	120/ 277VAC Watts 4W - 4Watts

Specification Features

Input Voltage	120/277VAC 60Hz
Input Rating	4.0W, 60mA
Operating Temperature	0°C to 40°C (32°F to 104°F)
Illumination	Long-life high-intensity LED's
Battery	Maintenance-free 3.6V NiCad battery

Dimensions



Part Number	A (Length)	B (Width)	C (Height)
TK-EE-7007	11.77 inches	1.75 inches	1.75 inches

