

Catalog #:	
Project :	
Type :	Date:
Notes:	

T8/T5 Led Tube

TKIEO-2ST8/T5-4FT Series

DESCRIPTION

The T8/T5 Led Tube are the functional and multi-purpose channel family that incorporates premium performance and construction durability.

APPLICATIONS

This Luminaries widely used at garages, stairwells, storage areas and other wet and harsh environments.

Product Details

Product ID	Materials	Wattage	Lm/W	CCT
TKIEO-2ST8/T5-4FT-6W-4K-F	PC cover	6W	170Lm/w	4K
TKIEO-2ST8/T5-4FT-10W-4K-F	Glass	10W	180Lm/w	4K
TKIEO-2ST8/T5-4FT-16W-4K-C	Glass	10W	180Lm/w	4K
TKIEO-2ST8/T5-4FT-16W-4K-C1	Glass	16W	180Lm/w	4K
TKIEO-2ST8/T5-4FT-17W-5K-C	Glass	17W	180Lm/w	5K



Specification Features

Controls / Dimming

Aluminium body + PC c over Mount Ceiling Flicker Motion Sensor, Emergency Backup PIR sensor. 50,000 working hours

Warranty

5 Years Limited Warranty. See warranty documentation for more information.

Certification

It complies with 80+, ETL, CE, RoHS and 5 years warranty

Installation / Mounting

It is easy to install with the help of a universal mounting plate pre-installed at the bottom. Instant start w/NO humming. Optional surface or suspended mounted

Ordering Information

Example: TKIEO-2ST8/T5-4FT-6W-4K

TKIEO	2ST8/T5	4	6W	4K	F
Brand	Series	Length	Watts	Color	
TKIEO	2ST8/T5 2 Side T8/T5	4 FT	6 W = 6 Watt 10 W = 10 Watt 16 W = 16 Watt 17W = 17 Watt	4K - 4000K (Natural White) 5K - 5000K (Daylight White)	F = Frosted Lens C = Clear Lens

Lighting Parameters

Input Voltage	100-277V AC
CRI	140 to 80
Luminous efficacy	Up to 180Lm/w
Beam Angle	120°
Wattage	6W / 10W / 16W / 17W
PF	>0.9
Working temperature	-4°F - +122°F
Life span	50,000 Hrs

Product Dimension

