



XTRAFLEX Liquidtight Conduit Tubing & Fittings

T&B Catalog Number:

UPC Number: EFC050
 Status: 78621078961
 Description: Active

1/2 in. black corrugated PVC flexible tubing.

Features

- Maximum flexibility in tight applications.
- Extremely fast installation
- Liquidtight with specified fittings.
- Good tensile strength provides excellent pullout protection and smooth inner diameter allows easy wire pulling.

Application

Protection of fiber optic cable, installation of instrumentation and control cable, indoor and outdoor lighting, packaging equipment, marine and ship-board wiring, and flexing-component wiring protection on robots, graphic arts equipments, etc.

General

Material: PVC
 Color: Black
 Working Temperatures: -18 C to +60 C

Dimension Information

Size (inches): 1/2
 I.D. - Minimum (inches): 0.622
 I.D. - Maximum (inches): 0.642
 O.D. - Minimum (inches): 0.82
 O.D. - Maximum (inches): 0.84

Packaging

T&B Order Multiple: 100
 Package in Units: 100
 T&B Sold in UOM: Feet
 T&B Weight Per UOM: 10.3 lbs. per 100

Application Support

Guide to Nonmetallic Conduit Applications Available on Website
 XTRAFLEX System Specifications Available on Website

Certifications

RoHS Compliance: Yes

Certifications



File Nbr:
 E 96548



For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com